

Rainier Fiber™



Rainier Fiber™ Bonded Fiber Matrix

DESCRIPTION

Rainier Fiber™ Bonded Fiber Matrix consists of long strand 100% virgin wood fibers along with a high strength, non-toxic, hydrocolloid-based and cross-linked organic tacifier giving the product extra holding power. No synthetic or plastic fibers, which are not naturally biodegradable, are added or blended into the pure wood fiber. The system sprays on like mulch and forms a blanket that adheres to the soil surface. When dry, the blanket matrix is porous, erosion resistant and protects the soil surface. The matrix retains its integrity and soil protection despite re-wetting. When applied over the soil surface, the wood fibers twist and interlock with each other and the soil as they dry. With the added tacifier, the holding power of the fiber to the soil is much stronger than mulch without tacifier, thus providing increased erosion protection.

Rainier Fiber™ Bonded Fiber Matrix is 100% biodegradable and is non-toxic to fish and wildlife.

ADVANTAGES

- Stronger bonding of the fibers to the soil, increasing erosion protection.
- No synthetic or plastic fibers, which do not naturally biodegrade, are added to the fiber.
- Mat blanket retains integrity after repeated rains.
- Conforms to all surface contours. Eliminates tenting and rilling.
- Has no germination or growth inhibiting factors.
- High temperature 177°C (350°F) steam and thermo-mechanical refining sterilizes the fiber.
- No viable noxious or other plant seed in the fiber. All seeds are sterilized.
- Tacifier hydrates quickly in the slurry.
- Tacifier additive is homogeneously mixed with the fiber. It's all in the same bag.

Rainier Fiber™ Bonded Fiber Matrix is fast to load in hydroseeding equipment from easy-to-handle plastic bags. The fibers are sized for maximum loading in a tank, and they make a homogeneous slurry of water, seed and fertilizer. The fibers remain in suspension during agitation and pumping, and the slurry does not dewater when doing hose work.

The green color allows the operator to apply an even application of material over the soil surface. The green dye added to the fiber during manufacture is non-toxic to fish or wildlife.

PRODUCT FEATURES

- Made from selected, fresh cut, clean, 100% whole wood chips.
- Fiber stays in uniform suspension and blends with seed and fertilizer.
- Goes into slurry quickly.
- Forms a stable erosion control mat.
- Provides favorable micro-climate for fast seed germination.
- Pumps easy in hydromulching machines.
- BFM has no growth inhibiting factors.
- Fibers decompose after plants have established.

PRODUCT SPECIFICATIONS

Rainier Fiber™ Bonded Fiber Matrix is manufactured to specific fiber sizes in a heat controlled environment to provide best job-site performance. The virgin wood chips are softened by high temperature 177°C (350°F) steam, and the thermo-mechanical refining process produces long, soft, woolly fibers. A minimum of 25% of the fibers are 10 mm (3/8 inch) long and a minimum of 50% are retained on a 710 µm (No. 25) sieve. The fibers have physical features that tend to intertwine with each other, thus forming a more protective blanket. The BFM is totally free from lead paint, printing ink, varnish, petroleum products, seed germination inhibitors, or chlorine bleach.

Composition: Refined virgin wood fiber (total weight basis).....	90%
Proprietary cross-linked binder (total weight basis).....	10% min.
Moisture content (total weight basis)..... ASTM D-644	12.0% ± 3%
Organic Matter (oven dry weight basis)..... ASTM D-586	97.0%
Ash Content (oven dry weight basis)..... ASTM D-586	3.0%
pH @ 3% concentration in water	SW846 9045
Water holding capacity (minimum)	ASTM D-7367.....
Color	Green

PERFORMANCE PROPERTIES

Percent Effectiveness:	Test Method: ASTM D-6459 (modified).....	> 99%
Seed Germination Enhancement	Test Method ASTM D-7322	>500%
Functional Longevity	Test Method Observed	>12Mo
Erosion Control Technology Council HECP Classification		Long Term

PACKAGING

The BFM is compressed and sealed in heavy duty plastic bags that have a UV inhibitor. Bag weight is a nominal 50 lbs. (22.7 kg) net and measures 10 x 19 x 29 inches. There are 40 bags per pallet which is made into a tight, stretch-wrapped unit.

APPLICATION

Recommended Rates: 3,000 lbs/acre -- 2H: 1V slopes.
 3,300 to 4,000 lbs/acre – slopes steeper than 2H: 1V
 depending on site conditions.

Apply the BFM to make a uniform mat. Green dye is added to help the applicator maintain uniform coverage. Spray from two opposite directions to avoid light coverage, or shadowing, on the back side of ridges, rocks and depressions. Application should be made sufficiently in advance of rainfall to allow some drying time. Allow enough drying time between applications so some dry spots are showing on the surface of the mat.

FOR MORE INFORMATION PLEASE CONTACT:

Fiber Marketing International, Inc.
 11111 EAST TRENT
 SPOKANE, WA 99206
 800-426-6002 or 509-927-4071
 509-927-2330 FAX
 www.fibermarketing.com