

Rainier Extreme DE Effective Date: January 18, 2021

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Rainier Extreme DE

CHEMICAL NAME/SYNONYM: Wood Fiber Mulch with a Tackifier Mixture

Thermo-Mechanical Wood Pulp with a Tackifier Mixture

MANUFACTURER: Rainier Veneer, Inc.

ADDRESS: PO Box 1250

Graham, WA 98338

EMERGENCY PHONE: Tel: (253) 846-0242

Fax: (253) 846-0220

Email: tjohnson@rainierveneer.com

RECOMMENDED USE: Hydroseeding Mulch for Erosion Control and Revegetation.

SECTION 2: HAZARDS IDENTIFICATION

Emergency Overview: This product does not contain regulated levels of hazardous ingredients as defined in OSHA STANDARD

29 CFR 1910.1000.

Rainier Extreme DE is a 100% wood fiber treated with green colorant for application control. A tackifier is blended with the fiber for increased erosion control. Rainier Extreme DE mulch presents little or no hazard to humans and has low acute oral and dermal toxicity. This product does not present any unusual hazard if involved in a fire.

OSHA HAZARD CLASSIFICATION: WOOD DUST - Category 3

OSHA HAZARD PICTOGRAM:



SIGNAL WORD: WARNING

HAZARD STATEMENTS:

H320: Dust may cause eye irritation from prolonged exposure.

H335: Dust may cause respiratory irritation from prolonged exposure.

PRECAUTIONARY STATEMENTS:

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from sparks, open flames and other ignition sources. No smoking.

P261: Avoid breathing dust. Use face mask

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to remove – continue rinsing.

PAGE 1 OF 4 DATE: 01/18/2021

Rainier Extreme DE Effective Date: January 18, 2021

PRECAUTIONARY STATEMENTS: (cont.)

P370+P378: In case of fire use water to extinguish.

P391+P501: Collect spillage and use or dispose of contents/container in accordance with local regulations. .

Other hazards which do not result in classification: None

CAS #..... None OSHA TWA PEL-STEL.....10mg/m³

ACGIH TLV......5 mg/m³ (respirable)

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence do not require reporting in this section. Occupational exposure limits are listed in Section 8.

Thermo-mechanically Refined Wood Fiber @ 12% Moisture...... >89.8% Green Colorant<0.2% Polysaccharide & Cross-linked Tackifier......10% CAS#......9000-30-0

SECTION 4: FIRST AID MEASURES

Material is primarily a Nuisance Dust

Routes of Entry......Inhalation, skin contact, eye contact

Effect of Acute Exposure:

Persons with respiratory problems should avoid breathing dust. Use a dust mask.

Ingestion May cause vomiting or diarrhea.

Carcinogenicity Listings:

NTP not listed IARC Monographs.....not listed OSHA: not listed

SECTION 5: FIRE-FIGHTING MEASURES

Flash Point.....>550F

Flammability Limits: LEL.....Not Applicable See Unusual Fire and Explosion Hazards below.

UEL.....Not Applicable

Extinguishing Media......Water: Caution: Wet product will be very slippery.

Special Fire Fighting ProceduresNone. May produce carbon monoxide, carbon dioxide and aldehydes.

Unusual Fire and Explosion Hazards A concentration of 40,000 mg/m³ is often used as the lower explosive limit for wood dusts in the presence of a flame or spark. Limit depends on moisture content and

particle diameter.

SECTION 6: ACCIDENTAL RELEASE MEASURES

General: Rainier Extreme DE is biodegradable and will not cause damage to trees or vegetation.

Land Spill: Clean up spilled material. Dispose in accordance with Federal, State and local regulations. No personal

protective equipment is required.

Water Spill: Rainier Extreme DE mulch will not cause contamination of local waters. The mulch is non-toxic and not

harmful to animal, aquatic, fish or plant life. Caution: Wet product will be very slippery.

SECTION 7: HANDLING AND STORAGE

Storage: Ambient dry indoor conditions are recommended. If outside storage, cover to protect from rain. Do Not store near heat or flame source. No smoking in the storage area. No special handling precautions required. To maintain package integrity, stock should be used on a "first in, first out" basis.

PAGE 2 OF 4 DATE: 01/18/2021

Rainier Extreme DE Effective Date: January 18, 2021

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory Protection...........Use NIOSH approved respiratory masks.

Eye Protection......Use goggles or eye glasses **Hand protection**......If sensitive, wear gloves

Other Protective clothing......None

Ventilation Indoors......Normal ventilation. If exhaust ventilation is used to keep dust concentrations below

permissible levels, exhaust should be directed to a dust collection system.

Work/Hygiene Practices......Follow good hygiene practice.

Occupational Exposure Limit: Wood Dust:

OSHA: PEL-STEL 10 mg/m³ ACGIH: TLV 5 mg/m³ (respirable) Cal OSHA: PEL 5 mg/m³

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance & Odor......Finely divided green fibers, slight wood odor

Boiling Point (F)......Not Applicable

PH4.9 **Flash Point**>550 F

Solubility in Water..... Insoluble, but Dispersible

Flammability......Solid. Initial ignition, then slow smoldering embers.

Flammability Limits.....LEL Not Applicable. See Unusual Fire and Explosion Hazard, Section V.

Auto-ignition Temperature.....Not Available Decomposition Temperature....Not Applicable

Viscosity......Not Applicable. Material is a solid.

SECTION 10: STABILITY AND REACTIVITY

StabilityStable

Avoid extreme heat and flame and contact with oxidizing agents.

Hazardous Polymerization......Will not occur

SECTION 11: TOXICOLOGICAL INFORMATION

Rates of Exposure: Inhalation is the most significant route of exposure in occupational and other settings. Dermal exposure is not usually a concern because Rainier Extreme DE mulch is not absorbed through intact skin.

Inhalation: Rainier Extreme DE mulch is not likely to be hazardous by inhalation.

Eye Contact: Rainier Extreme DE mulch is non-irritating to eyes in normal industrial use.

Skin Contact: Rainier Extreme DE mulch does not cause irritation to intact skin.

<u>Ingestion:</u> Products containing *Rainier Extreme DE* mulch are not intended for ingestion. *Rainier Extreme DE* mulch has a relatively low acute toxicity. Swallowing large amounts may cause gastrointestinal symptoms.

Cancer: Rainier Extreme DE mulch is not considered a carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

The inherent design of *Rainier Extreme DE* is for use in revegetation and is not harmful to ecological systems. Refer to Section 6 for clean-up in case of accidental spill.

PAGE 3 OF 4 DATE: 01/18/2021

Rainier Extreme DE Effective Date: January 18, 2021

SECTION 13: DISPOSAL CONSIDERATIONS

<u>Disposal Guidance:</u> Small quantities of *Rainier Extreme DE* mulch can usually be disposed of at Municipal Landfill sites. No specific disposal treatment is required, but refer to state and local regulations for applicable site-specific requirements.

Tonnage quantities of product are not recommended to be sent to landfills. Such product should, if possible, be re-used for an appropriate application.

<u>California Hazardous Waste Designation:</u> California identifies substances with acute LD50's less than 5000 mg/kg as "hazardous wastes". *Rainier Extreme DE* mulch is therefore not a "hazardous waste" if spilled in California. Refer to Regulatory Information for additional information.

SECTION 14: TRANSPORT INFORMATION

<u>DOT Hazardous Material Classification:</u> Rainier Extreme DE mulch is not a U. S. Department of Transportation (DOT) Hazardous Material and is not regulated.

<u>DOT Hazardous Substance Classification:</u> Rainier Extreme DE mulch is not a DOT Hazardous Substance and is not regulated.

<u>International Transportation:</u> Rainier Extreme DE mulch has no U. N. Number, and is not regulated under international rail, highway, water, or air transport regulations.

SECTION 15: REGULATORY INFORMATION

National Fire Protection Association (NFPA) Classification:

Health - 0 Flammability - 1

Reactivity - 0*

Hazardous Materials Information Systems (HMIS):

Red: (Flammability) - 1 Yellow: (Reactivity) - 0

Blue: (Acute Health) - I*

*Chronic Effects

SECTION 16: OTHER INFORMATION

ADDITIONAL INFORMATION

Definition of Common Terms:

ACGIH = American Conference of Governmental Industrial Hygienists

C = Ceiling Limi

CAS# = Chemical Abstracts System Number

IARC = International Agency for Research on Cancer

MSHA = Mining Safety and Health Administration

NAP = Not Applicable
NAV = Not Available

NIOSH = National Institute for Occupational Safety and Health

NTP = National Toxicology Program

OSHA = Occupational Safety and Health Administration

PEL = Permissible Exposure Limit

STEL = Short-Term Exposure Limit (15 minutes)

TLV = Threshold Limit Value

TWA = Time-Weighted Average (8 hours)

Information presented herein has been compiled from sources considered dependable and is accurate and reliable to the best of our knowledge and belief, but it is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patents or in violation of any laws or regulations. It is the user's responsibility to determine the suitability of any material for a specific purpose and adopt necessary safety precautions. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

PAGE 4 OF 4 DATE: 01/18/2021